

PRODUCT INTRODUCTION

1.Package Contents:

- LED Bulb X2
- User Manual X1

2.Product specifications

Operating voltage	DC(11-18V)
IP rating	IP68
Color temperature	6000 - 6500K
Operating temperature	-40°C - 85°C
LED chips	High-brightness LED chips
Heat sink	6063 aluminum alloy

USER INSTRUCTIONS

- Please purchase the product through official channels, otherwise we won't provide after-sales service.
- As the product has small & sharp parts, please keep it away from children.
- After receiving the product, please carefully check whether it is damaged or any part is missing. If there is any problem, please contact Customer Service .
- This product is only fit for vehicles which use 12V batteries. High voltage may cause damage.

INSTALLATION INSTRUCTIONS


1.Important Notes:

- ① Please light-up the bulb before installation.
- ② The OE halogen bulb would be extremely hot for a quite long time after shutting down the engine. To avoid burns, please wait at least 2 hours before replacing the lamps.
- ③ Wear gloves while replacing the lamps, and do not touch the LED chips.
- ④ If the lamps do not light-up . please unplug the power line. connect it reversely and try again.

2. Models: H11/H10/9006



Installation instructions



Step 1: Remove the bulb compartment rubber cover and disconnect the original vehicle connector.



Step 3: Insert the LED bulb into the bulb compartment.Align the tab parts of the LED bulb with the groove sections of the locking ring.



Step 2: Turn the bulb counter-clockwise and then remove the original bulb.



Step 4: While pushing the bulb down, turn it clockwise until it cannot turn anymore and then ensure the LED bulb is securely in place.




Step 5: Attach the LED bulb connector with the original vehicle connector and reinstall the rubber cover(if present).

3. Models: 5202/PSX24W




Installation instructions



Step 1: Remove the bulb compartment rubber cover and disconnect the original vehicle connector.




Step 2: Press the tabs on both sides of the halogen bulb and remove the original bulb.



Step 3: Insert the LED bulb into the bulb compartment.Align the tab parts of the LED bulb with the groove sections of the locking ring.



Step 4: Push the snap ring without rotating, ensuring that the assembly is fully aligned in the correct position without any looseness.



Step 5: Attach the LED bulb connector with the original vehicle connector and reinstall the rubber cover(if present).

FAQ

1.Q: The model of lamps I purchased is different from my OE halogen lamps.
Can I get an exchange for the correct model?

A: The main reasons:

(1) Amazon Confirmed Fit system is not 100% accurate.

(2) Your fog lights assembly is not an OE part.

Please double check the model of your OE halogen bulb. And contact
our Customer Service for an exchange.

2.Q: The size of the lamps is not correct, they're either too long or too wide,
and LED lamps can't be installed into the fog lights assembly. How can I
get proper size lamps for my car?

A: Some LED lamps are not in a 1:1 ratio with the OE halogen bulbs. The
large base is for better heat dissipation and prolonging the life of the lamps.
If the lamps are not suitable for installation, please contact the Customer
Service.

WARRANTY DESCRIPTION

Thank you for purchasing our products. All of our products are manufactured
with best quality control ; To protect your rights, you can extend the warranty
period for 6 months by contacting us via the links below or send us a email.

Extended warranty period:

E-mail: support@sealight-led.com

Links: <https://sealight-led.com/membership>

TECHNICAL SUPPORT & SERVICE TEAM

E-mail: support@sealight-led.com

Tel : (+1)805-538-4353

If there is any questions about the bulbs, contact our service team for help.

Made In China

SEALIGHT™

SEALIGHT™

**LED
LIGHTING** 

User Manual

 www.sealight-led.com

 support@sealight-led.com